

HAVi Technical Data Sheet



Features and Benefits

A Hand Arm Vibration Monitor designed to help compliance with The Control of Vibration at Work Regulation 2005.

- Accurately captures the trigger time that a tool is used and automatically calculates and displays the corresponding HSE points accumulated.
- Easily transferred between tools, monitors are fitted using either the fabric or cable tie supplied.
- Programmed on site by operators who enter the vibration magnitude for the tool they are using - No additional software required reducing installation costs.
- A truly operator focused product. Aids training and informing of HAV exposure.
- Optional heavy duty case for maximum protection.

CE 1180

WEEE compliant. Patent applied for.

Temperature

The HAVi has a working temperature range of -20°C to 40°C.

Power Cell

Battery powered. Estimated life 1,000 trigger time hours.

Dust and Waterproof

IP65 screws and seals.
Ruggedised rubber keys.

to order now call: **0116 278 8289**
or visit our website: **havcontrol.co.uk**



Technical Specification

Technical Support Services

Tool box talks, training days, bespoke training packages carried out by an IOSH certified professional.

On site tool testing to BS5349.

Audit of policies and procedures to ensure compliance with the "Control of Vibration at Work Regulation 2005."

Dimensions

Item	HAVi Unit	HAVi Heavy Duty Case
Part No.	0010	0011
Height	20mm	25mm
Width	69mm	74mm
Depth	35mm	38mm
Weight	30g	51g
LCD Screen size	36mm	-

HAVi Pack Contents:

- x1 HAVi Unit
- x1 Velcro Strap
- x2 Cable Ties
- x3 Traffic Light Bands
- x1 Instruction Leaflet



Barcoded Retail Packaging



Optional Extra Heavy Duty Casing



Part No.: HD Case